

# PRODUCT INFORMATION

## **Ultra1Plus Full Synthetic ATF Universal**

### **Product Description**

Formulated with synthetic base stocks and premium performance additives, **Ultra1Plus** Full Synthetic ATF Universal is a premium high-viscosity, heavy-duty synthetic transmission lubricant. This product contains a premium performance additive package designed for excellent oxidation stability and thermal resistance as well as excellent friction modification properties. **Ultra1Plus Full Synthetic ATF Universal** is a universal automatic transmission lubricant which is suitable for use in nearly all makes and models of automatic transmissions including passenger cars, light trucks, heavy-duty trucks, commercial vehicles, as well as off-road vehicles.



#### Suitable for Use

Allison C-3, C-4, TES-295, TES-389	Honda/Acura
GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H	Hyundai
Ford MERCON®, MERCON® V (except Ford Type F)	Jaso
Chrysler (Mopar) ATF +3, ATF +4	Mercedes
Toyota/ Lexus T-II, III, IV and WS	Mitsubishi
Volvo	Nissan/Infinity
Voith	CAT TO-2
BMW	VW
ZF	



#### **Typical Properties**

Parameter	Result
Appearance	Red, Dyed Liquid
Viscosity @ 40°C, cSt, ASTM D445	35.0
Viscosity @ 100°C, cSt, ASTM D445	7.30
Viscosity Index, ASTM D2270	180
Brookfield Viscosity @ -40°C, ASTM D2983, cP	11,000
Pour Point, °C, ASTM D97	-54
Flash Point, °C, ASTM D92	210



NOT recommended for use in Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT) or applications that require a non-friction modified ATF, such as Ford Type F or Ford Type G (used in certain European transmissions).

Revised: 05/28/2020

