

PRODUCT INFORMATION

Ultra1Plus SAE 10W-30 Synthetic Super Tractor Oil Universal Fluid

Product Description

Ultra1Plus SAE 10W-30 Synthetic Super Tractor Universal Fluid is a premium multipurpose tractor lubricant designed for use in engines, transmissions, final drives and hydraulic systems of various off-road equipment. This multi-use fluid is formulated with group II paraffinic base stock and a premium performance additive package which provides robust anti-wear, antioxidant, anti-foam, and detergent properties.



Suitable for use in applications which require a Caterpillar TO-4 oil in the SAE 10W or SAE 30 viscosity grades.

Further, specialty friction modifiers minimize chatter, sticking or slipping for wet brakes and power take-off clutches. This multi-grade fluid is designed for year-round performance in all seasons.

Suitable for Use

API CF-4 API CF

API CE API CD/SF

API GL-4 Massey Ferguson MF 1145, 1144

Massey Ferguson MF 1139 (10W-30) John Deere J27C

ZF TE ML 06B, 07B Ford M2C 159 B/C

Ford New Holland 82009201/2/3 ZF TE-ML 07C



Product Features & Benefits

SAE J300 Viscosity Grade	10W-30
Appearance	Amber transparent liquid
Viscosity @ 40°C, cSt, ASTM D445	67.25
Viscosity @ 100°C, cSt, ASTM D445	10.5
Viscosity Index, ASTM D2270	145
CCS Apparent Viscosity, cP, ASTM D5293	5,500@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	21,000@-20°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-35



Revised: 02/23/2020





PRODUCT INFORMATION

