

PRODUCT INFORMATION

Ultra1Plus SAE 10W-40 Synthetic Blend Motor Oil API SN

Product Description

Ultra1Plus Synthetic Blend Motor Oils, SAE 10W-40 API SN is formulated with a blend of conventional and synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines in both normal and extreme operating conditions. This oil exceeds the performance requirements of API SN.

Product Features & Benefits

- Helps prevent deposits and sludge buildup to enable long engine life.
- Provides overall lubrication and wear protection performance for many driving styles.
- Delivers outstanding performance during the maximum oil change interval recommended in a vehicle's owner's manual.
- Provides better control of emissions.

Product Codes

Presentation	SKU	UPC
Quart	USB1040SNL	810050650724
Gallon	USB1040SNG	810050650717

Exceeds Performance Requirement

API SN	API SL
API SM	API SJ





Typical Properties

SAE J300 Viscosity Grade	10W-40
Appearance	Amber Transparent Liquid
Viscosity @ 40°C, cSt, ASTM D445	100.25
Viscosity @ 100°C, cSt, ASTM D445	14.5
Viscosity Index, ASTM D2270	150
CCS Apparent Viscosity, cP, ASTM D5293	5,600@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	21,000@-30°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-40

Revised: 05/28/2020

