



PRODUCT INFORMATION

Ultra1Plus SAE 75W-90 Synthetic Gear Oil, API GL-5

Product Description

Ultra1Plus SAE 75W-90 Synthetic Gear Oil, API GL-5 is formulated with synthetic base oils and specialty performance additives to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions. Specialty anti-scuffing additives and friction modifiers provide advanced protection and lubricity in extreme pressure conditions. Additionally, **Ultra1Plus SAE 75W-90 Synthetic Gear Oil, API GL-5** is highly shear stable while also resisting rust, oxidation, foaming, and varnish.

Ultra1Plus SAE 75W-90 Synthetic Gear Oil, API GL-5 is designed for use in all seasons and exceeds the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5.

Product Code

Presentation	SKU	UPC
Quart	UFS7590GL5L	810050654142
Gallon (4 QT)	UFS7590GL5G	810050654135
5 Gallon Pail	UFS7590GL5P	810050654128
55 Gallon Drum	UFS7590GL5D	810050654111

Exceeds performance requirements

API GL-5

Typical Properties

SAE J300 Viscosity Grade	75W-90
Appearance	Yellow Transparent Liquid
Viscosity @ 40°C, cSt, ASTM D445	113.2
Viscosity @ 100°C, cSt, ASTM D445	15.5
Viscosity Index, ASTM D2270	145
Pour Point, °C, ASTM D97	-50
Flash Point, °C, ASTM D92	205



Revised: 05/28/2020

LOVE YOUR MACHINE

www.ultra1plus.com @ultra1plus

