



PRODUCT INFORMATION

Ultra1Plus SAE 80W-90 Gear Oil, API GL-5

Product Description

Ultra1Plus SAE 80W-90 API GL-5 GEAR OIL is formulated with high viscosity-index, paraffinic base oil and specialty performance additives. API Category GL-5 designates the type of service characteristic of gears, particularly hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions. Specialty anti-scuffing additives and friction modifiers provide advanced protection and lubricity in extreme pressure conditions. Additionally, **Ultra1Plus SAE 80W-90 API GL-5 Gear Oil** is highly shear stable while also resisting rust, oxidation, foaming, and varnish.



Product Features & Benefits

- Extended gear and bearing life due to minimal deposits.
- Longer seal Life.
- Increased load-carrying capability.
- Contribution to reduced maintenance cost and longer equipment life.
- Helps to reduce operating costs



Exceeds Performance Requirements

API GL-5
SAE J2360

Product Codes

Presentation	SKU	UPC
Quart	UC8090GL5L	810050654029
Gallon (4 QT)	UC8090GL5G	810050654012
Pail	UC8090GL5P	810050654005

Typical Properties





PRODUCT INFORMATION

SAE J306 Viscosity Grade	80W-90
Appearance	Amber Liquid
Viscosity @ 40°C, cSt, ASTM D445	139.8
Viscosity @ 100°C, cSt, ASTM D445	15.5
Viscosity Index, ASTM D2270	115
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-30

Revised: 05/28/2020

