

Ultra1Plus CVT Universal Full Synthetic

Suitable for Use

Audi	TL 52180	G052 180 A2	G052 516
BMX	83 22 0 136 376	83 22 0 429 154 (EZL 799A)	
Chrysler	CVTF+4		
Daihatsu	Amix CVTF-DC	Amix CVTF-DFE	Fluid TC
Dodge/Jeep	NS-2	CVTF+4/MOPAR CVTF+4	
Ford	CVT WSS-M2C-933-A / XT-7QCFT		CFT23 CFT30 / Mercon C
Honda	Multimatic Fluid (HMMF)		HCF-2
Fujijyuuko	i-CVTF FG		
GM/Saturn	DEX-CVT		
Hyundai / Kia	SP-CVT-1		
Lexus	Fluid TC		Fluid FE
Nissan	NS-1		NS-2
Mazda	CVTF 3320		
Mercedes Benz	CVT28 / MB 236.20		
Mini Cooper	EZL 799A / ZF CVT V1		
Mitsubishi	DiaQueen CVTF-J1		DiaQueen CVTF-J4
Punch	EZL 799A		
Shell	Green 1V		
Subaru	i-CVTF	Lineartronic CVTF	K0425Y0710
Subaru	CV-30	e-CVTF	
Suzuki	CVTF 3320	TC	NS-2
Suzuki	CVTF Green 1	CVTF Green 2	
Toyota	Fluid TC	Fluid FE	
Volvo	CVT 4959		
VW	TL 52180	G 052 180 A2	G 052 516



Typical Properties

Parameter	Result
Appearance	Red, Dyed Liquid
Viscosity @ 40°C, cSt, ASTM D445	34.0
Viscosity @ 100°C, cSt, ASTM D445	7.2
Viscosity Index, ASTM D2270	183
Brookfield Viscosity @ -40°C, ASTM D2983, cP	12,250
Pour Point, °C, ASTM D97	-52
Flash Point, °C, ASTM D92	195

Revised: 05/28/2020