



PRODUCT INFORMATION

Ultra1Plus ISO 68 Conventional AW Hydraulic Oil

Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, **Ultra1Plus AW Hydraulic Oil ISO 68** exhibit excellent oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures. The comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency. Acceptable for a wide-range of applications, **Ultra1Plus AW Hydraulic Oil ISO 68** resist oxidation, rust, corrosion, foaming, varnish, and wear.

Exceeds Performance Requirements

Parker Denison HF-0, HF-1, HF-2	U.S. Steel 127
MAG IAS P-69 (ISO 68)	U.S. Steel 136
GM LS-2	Bosch Rexroth RD90220
JCMAS HK	SAE MS1004

Product Code

Presentation	SKU	UPC
5 Gallon Pail	UC68AWP	810050654968
55 Gallon Drum	UC68AWD	810050654951
265 Gallon Tote	UC68AWT	810050654944

Typical Properties

ISO VG	68
Appearance	Yellow Transparent Liquid
Viscosity @ 40°C, cSt, ASTM D445	68.0
Viscosity @ 100°C, cSt, ASTM D445	8.97
Viscosity Index, ASTM D2270	105
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-27



Revised: 05/28/2020

LOVE YOUR MACHINE

www.ultra1plus.com @ultra1plus

