



# PRODUCT INFORMATION

## Ultra1Plus SAE 5W-30 Full Synthetic Motor Oil, API CK-4/SN

### Product Description

**Ultra1Plus SAE 5W-30 Full Synthetic Heavy-Metal Motor Oil, API CK-4/SN** is formulated with synthetic base oils and a premium additive package. This oil is designed for use in for use in high-speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards as well as for previous model year diesel engines. This oil is especially effective at sustaining emission control system durability where particulate filters and other advanced aftertreatment systems are used. **Ultra1Plus Heavy-Duty SAE 5W-30 Full Synthetic Motor Oil, API CK-4/SN** provide enhanced protection against oil oxidation, viscosity loss due to shear, and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low- and high-temperature properties, and soot-related viscosity increase.



### Product Codes

Presentation	SKU	UPC
5 Gallon Pail	UC50CH4SGP	810050651363
55 Gallon Drum	UC50CH4SGD	810050651356
265 Gallon Tote	UC50CH4SGT	810050651349

### Exceeds Performance Requirements

API CK-4, CJ-4, CI-4 Plus, CI-4, CH-4	API SN, SM, SJ, SF	ACEA E9-12
Cummins CES 20086	DDC 93K222	Caterpillar ECF-3
Renault Trucks RLD-4	Mack EOS 4.5	MTU Type 2.1
Deutz DQC III-10 LA	Daimler MB 228.31	Volvo VDS-4.5
Ford WSS-M2C171-F1		

### Product Features & Benefits

SAE J300 Viscosity Grade	5W-30
Appearance	Amber transparent liquid
Viscosity @ 40°C, cSt, ASTM D445	61.25
Viscosity @ 100°C, cSt, ASTM D445	10.8
Viscosity Index, ASTM D2270	170
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-35°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-42
Total Base Number, mg KOH/g, ASTM D2896	9

Revised: 05/28/2020

LOVE YOUR MACHINE

www.ultra1plus.com @ultra1plus

